DESTROYIT® 2240

Compact, entry model Deskside shredder.

Security level P-2	4 mm strip-cut (3/16 inch)	
Sheet capacity:	10-12*	
Security level P-4	3 x 25 mm cross-cut (1/8 x 1 inches)	
Sheet capacity:	5-6*	

^{*}Certified using 8 1/2" x 11" 20 lb. bond and recommended power supply.



Transparent safety shield in the feed opening. Automatic power cut-off when shredder head unit is removed from impact-resistant plastic shred bin (cross-cut model). Double protection against overheating. Automatic start and stop controlled by photo cell. Multifunction control switch with pilot light. High quality, hardened steel cutting shafts take staples and paper clips (strip-cut model takes credit cards). Lifetime warranty on the cutting shafts. Quiet and powerful single phase motor. Fully enclosed gear box housing. Integrated handle for lifting shredder head unit from shred bin.

Specifications

Shred volume, gallons	5
Feed opening, inches	8 3/4
Electrical requirements, volts	115
Maximum horsepower	1/5
Dimensions (D x W x H), inches	8 1/2 x 13 1/2 x 17 3/4
Shipping weight, pounds	16 (sc), 18 (cc)

WWW.MBMCORP.COM TEL: 800-223-2508

WWW.IDEAL-MBM.COM TEL: 800-387-2528





DESTROYIT® 2240

Features



SOLID STEEL CUTTING SHAFTS

High grade, hardened steel cutting shafts are milled in our Balingen factory and warranted for life.



SAFETY SHIELD

Transparent safety shield keeps fingers out of the feed opening.



MULTIFUNCTION SWITCH

Operation is controlled by a 3 position rocker switch in combination with a photo cell for automatic start and stop.



CONVENIENT HANDLE

The integrated handle is used to remove head unit from bin to empty shreds.















